



KR8HD Scarifier

No matter how you "kut" it, the Kut-Rite KR8HD Scarifier is a very versatile tool. With 160 pounds of centrally located quality engineering, the KR8HD will not jump out of the cut. Consider the KR8HD for general duty surface preparation, removal of concrete, thermo-plastic lines, paints, thin mil coatings, trowel marks, curled joints, sidewalk trip hazards, etc.

Features & Benefits

Extra-heavy construction for added stability and ballast.

Zero-depth height adjustment.

Drum centrally located under the motor for better balance and less vibration.

Side access drum assembly for quick and easy cutter changes.

Swiveling vacuum hook-up for virtually dust-free operation.

Laser cut front-mounted lifting handles make loading and unloading easy.

Tethered emergency pull cord for immediate motor shut off.

At more than 160lbs. The KR8HD is heavier than most 8 inch machines so it performs better on stubborn materials.

www.kutritemfg.com

KR8HD Scarifier



Steel / Solid Carbide

Result

Description



The KR8HD equipped with steel cutters is ideal for preparing concrete for a coating application and/or removal of various surface materials such as: carpet foam backing, adhesives, mastics, glues, rust from steel decks and some thin mil coatings. Use a solid carbide cutter to achieve similar results with over ten times the cutter life.

Carbide (TCT)

Result

Description



Equip the KR8HD with our standard carbide tip cutters for grinding, leveling, grooving, cleaning and general surface preparation. The standard carbide tip cutter is a very aggressive cutter designed for removing material fast.

Full Face™

Result

Description



The Full Face™ carbide tip cutter is ideal for removing pavement markings, epoxy, paint, adhesives, mastics, etc. Use the Full Face™ cutter for removal applications that require a flat even finish. The full face of the carbide tip provides 100% removal of surface material with minimal damage to the substrate.

Milling

Result

Description



Utilize the milling cutter for removing thick and soft materials such as: mastic, thermo-plastic, waterproofing membranes, cold plastic coatings, glues, etc... The milling cutter leaves the surface smooth and ready for preparation.

Models	HP	Power Source	Power Specs	Weight	Production sq ft
KR8G5.5 HD	5.5	Gas	Honda 5.5HP	162lbs	2-400/hr
KR8E2 HD	2	Electric	120/240 1PH 18/9FLA	190lbs	2-400/hr

All weights can vary based on cutter selection



Kut-Rite
27482 Northline Rd.
Romulus, MI 48174

www.kutritemfg.com

P:734.955.9311
P:877.786.5067 - Toll Free
F:734.955.9314