



SCB-1600 Chassis W/BH-16 Shotblasting Head Attachment

BW Manufacturing has produced the only shot blast/scarifying/diamond grinding machine on the market today. The SCB-1600 with BH-16 Shotblasting Head Attachment gives you unmatched production with efficient operation and low maintenance. The BH-16 is a state of the art blast head designed to eliminate problems inherent in competitive units. The BH-16 delivers a 16" blast width and also provides a feathered blasting edge enabling each successive path to overlap without excessive penetration; omitting the striping effect which is common to other competitive machines. The finished surface is ideal for thin-set applications, clear coatings, as well as having the power to give you an aggressive blast profile when needed. Designed with the operator in mind, the SCB-1600 with the BH-16 Shotblasting Head Attachment uses one control for all machine operations along with power steering, adjustable seat with arm rest and full visibility in front and behind either head attachment. Any operator will feel comfortable running the SCB-1600. With removable heads on the SCB-1600, all replaceable wear items are easily accessible. General maintenance can be made through the removable panels.



*The SCB-1600's Interim Tier 4 diesel engine is in compliance with emission standards in all 50 states.

SCB-1600 Specifications

<u>Interchangeable Heads:</u>	Shotblast Scarifier Diamond Grinder/Polisher
<u>Tires:</u>	Non-marking
<u>Length:</u>	112" (285cm)
<u>Width:</u>	56" (142cm)
<u>Height:</u>	62" (157cm)
<u>Weight:</u>	4480 lbs. (2032kgs)
<u>Engine</u>	
<u>(Interim Tier IV Diesel):</u>	73 hp
<u>Drive:</u>	Hydrostat
<u>Compressor:</u>	Liquid Cooled 13 cfm.
<u>Vacuum:</u>	2280 cfm.
<u>Steering:</u>	Power
<u>Collector Capacity:</u>	19.67 cubic ft. (.55 cubic meters)
<u>Aisle Width Min:</u>	78" (198cm) (Blastable Width)

Shotblaster Applications

- * Industrial Floors
- * Bridge Decks
- * Parking Decks
- * Highways
- * Line Stripes
- * Airport Runways & Hangers
- * Steel Decking



BH-16 Specifications

<u>Production Capacity†:</u>	2000 to 5000 sfh (185 to 464 sqm)
<u>Cleaning Path:</u>	16" (41cm) (4" & 5" Adaptors Available)
<u>Width with attachment:</u>	56" (142cm)
<u>Weight:</u>	760 lbs. (345kgs)
<u>Aisle Width Min:</u>	78" (198cm) (Blastable Width)

†Production rates achieved will be affected by variables specific to each job site. These figures are not guarantees of performance. For proper operation, the shot blasting unit must be used in conjunction with an appropriate dust collector.

Always wear appropriate eye, ear and respiratory protection for the application, as specified by OSHA regulations and your employer. Never operate or maintain equipment before reading and understanding the instructions for operation and maintenance. Obey all safety signs and instructions while operating or maintaining equipment.



BW Manufacturing, Inc.

3706 Mill Creek Drive NE
Comstock Park, Michigan 49321 U.S.A.

Phone: 616-447-9076 • BWMANUFACTURING.com

