



SCB-1600 Chassis W/SC-16 Scarifier Head Attachment

BW Manufacturing, Inc. has produced the only scarifying/shotblasting/diamond grinding machine on the market today. With a state of the art scarifying head that is self leveling to automatically adjust itself to different contours of the floor or pavement. You will achieve an accurate removal of thin mill coatings to 1/4" overlays. The SCB-1600 with the SC-16 Scarifier Head Attachment is ideal for use on rubber membranes, mastics, epoxy coatings, and line stripes. The SCB-1600 with the SC-16 Scarifier Head Attachment will put you ahead of the competition with its high production rates and large vacuum/collector system that eliminates dust and removes all material from the surface it is scarifying. Versatility is the key to the SCB-1600 with the SC-16 Scarifier Head Attachment. With quick change cages allowing you to go from steel to carbide cutters and to different cutting width cages in just minutes. Designed with the operator in mind, the SCB-1600 uses one control for all machine operations along with power steering, adjustable seat with arm rest, and full visibility in front and behind either head attachment. General maintenance can be made through the removable side and lid panels. Any operator will feel comfortable running the SCB-1600.



*The SCB-1600's Interim Tier 4 diesel engine is in compliance with emission standards in all 50 states.

SCB-1600 Specifications

<u>Interchangeable Heads:</u>	Shotblast Scarifier Diamond Grinder/Polisher
<u>Tires:</u>	Non-marking
<u>Length:</u>	112" (285cm)
<u>Width:</u>	56" (142cm)
<u>Height:</u>	62" (157cm)
<u>Weight:</u>	4480 lbs. (2032kgs)
<u>Engine</u> (Interim Tier IV Diesel):	73 hp
<u>Drive:</u>	Hydrostat
<u>Compressor:</u>	Liquid Cooled 13 cfm.
<u>Vacuum:</u>	2280 cfm.
<u>Steering:</u>	Power
<u>Collector Capacity:</u>	19.67 cubic ft. (.55 cubic meters)
<u>Aisle Width Min:</u>	78" (198cm) (Scarifying Width)

Scarifier Applications

- * Industrial Floors
- * Bridge Decks
- * Parking Decks
- * Highways
- * Line Stripes
- * Airport Runways & Hangers
- * Steel Decking



SC-16 Specifications

<u>Production Capacity:</u>	500 to 1500 sfh (46 to 139 sqmh)
<u>Cleaning Path:</u>	4" to 16" (10cm to 40cm)
<u>Width with attachment:</u>	56" (142cm)
<u>Weight:</u>	620 lbs. (281kgs)

†Production rates achieved will be affected by variables specific to each job site. These figures are not guarantees of performance. For proper operation, the shot blasting unit must be used in conjunction with an appropriate dust collector.

Always wear appropriate eye, ear and respiratory protection for the application, as specified by OSHA regulations and your employer. Never operate or maintain equipment before reading and understanding the instructions for operation and maintenance. Obey all safety signs and instructions while operating or maintaining equipment.



BW Manufacturing, Inc.

3706 Mill Creek Drive NE
Comstock Park, Michigan 49321 U.S.A.

Phone: 616-447-9076 • BWMANUFACTURING.com

